

FOR IMMEDIATE RELEASE

Savin Web Site: www.savin.com

CONTACT: Russell Marchetta

Savin

(973) 882-2075

russell.marchetta@ricoh-usa.com

Jennifer Kuhl

Peppercom

(212) 931-6111

jkuhl@peppercom.com

**SAVIN INTRODUCES THE C6055/C7570
DIGITAL IMAGING SYSTEM**

West Caldwell, N.J., January 29, 2008 – Savin today introduced the C6055 and C7570, two new, high performance, color multifunctional products (MFPs). These digital imaging systems deliver output and speeds beyond any other in their class regardless of the task including printing, copying, scanning and faxing.

Ideal for general office environments looking to cost effectively incorporate color into documents, the new Savin C6055/C7570 Series is also well suited for Central Reprographics Departments (CRDs), commercial print shops as well as graphic houses looking to enhance their current printing services. The Savin C6055/C7570 Series offers a versatile system that presents an array of document management functions coupled with print speeds of 55 pages per minute (ppm) full-color/60 ppm black-and white and 70 ppm full-color/75ppm black-and-white, respectively.

The Savin C6055/C7570 Series delivers sharp, vivid, and consistent color printouts and clear black-and-white documents at 600 dots per inch (dpi). In addition, Savin's new toner technology has smaller, more uniform particles, which produce sharp image definition and smooth transitions in gradients. To ensure consistent color throughout production, the Savin C6055/C7570 Series has a sequence of internal calibrations running in the background to maintain toner uniformity and registration.

This series addresses both the needs of the individual user as well as those of the company by including a user-friendly interface as well as advanced security technology features. Customers can utilize the large, full-color, LCD touch-screen control panel on the device to enter commands to further create ease-of-use.

To increase productivity and expedite wait time, the series offers warm-up times of less than two minutes and allows users to reload paper while print jobs are being processed. Furthermore, both MFPs have a maximum paper capacity of 7,400 sheets. In addition to the ability to manage access to the devices through codes and user-authentication capabilities, the C6055/C7570 Series uses encryption to protect data and documents in the devices that are sent over the network. The systems also support IP security protocols to encrypt every IP packet in the data stream for high-security applications.

The Savin C6055 standard model is available at the suggested retail price of \$29,800, while the Savin C7570 starts at \$37,800. For more information on Savin's full line of products, please visit www.savin.com.

About Savin

With its broad line of award winning network-ready digital output systems – including full color and black-and-white digital imaging system, color and black-and-white network laser printers, and fax machines – Savin is helping businesses of all sizes become more productive and efficient. The Business Technology Association (BTA) honored Savin with two 2005 “Channel’s Choice” awards, via a nationwide poll of office equipment dealers. Savin is a brand of West Caldwell, NJ-based Ricoh Americas Corporation. For more information, visit www.savin.com.

#

All referenced product names are the trademarks of their respective companies.

Savin C6055/C7570 System Specifications

Hardware Specifications	
Configuration	Console
Scanning Element	Flatbed with moving 3-line CCD array image-scanning
Toner	Chemical toner
Resolution (dpi)	600 dpi
Document Feeder	Standard 100-sheet ARDF
Printing Speed	MP C6055: 60 ppm B&W and 55 ppm Full-Color MP C7570: 75 ppm B&W and 70 ppm Full-Color
First Print Speed	MP C6055: 5.7 seconds B&W and 7.5 seconds Full-Color MP C7570: 4.9 seconds B&W and 6.4 seconds Full-Color
Warm-Up Time	MP C6055: 90 seconds or less MP C7570: 75 seconds or less
Dimensions (WxDxH)	29.5" x 33.5" x 43.1" (excluding ARDF)
Weight	656.9 lb. or less
Power Requirements	MP C6055: 120V, 60Hz MP C7570: 208V-240V, 60 Hz
Standard Paper Capacity	1 st Tray 1, 100 x 2 550 sheets x 2 nd and 3 rd Trays 100-sheet Bypass Tray 7,400 sheet standard maximum capacity
Automatic Duplexing	Standard on both models
Paper Size	5.5" x 8.5" to 12" x 18"
Paper Weight	Standard Trays 14 lb. Bond – 80 lb. Cover Duplex Tray 17 lb. Bond – 90 lb. Index Bypass Tray 14 lb. Bond – 110 lb. Cover
Controller Specifications	
Memory (RAM)	1,536MB (standard/maximum)
HDD	320GB (160GB x 2)

Standard Interface	Ethernet (100BaseTX10 Base-T), USB2.010/100Base-TX
Optional Interface	IEEE 1284, Wireless LAN (IEEE 802.11a/g), Bluetooth, Ethernet 1000 Base-T
Network Protocol	TCP/IP, IPX/SPX, SMB, AppleTalk
Operating Systems	Windows: 2000/XP/Server 2003/Vista, Netware: 3.12/3.2/4.1/4.11/5.0/5.1/6/6.5, Unix, Sun Solaris, HP-UX, SCO OpenServer, Redhat Linux, IBM, AIX, MAC: OS 8.6 – 9.2x, OS X 10.1 or later
PDL	RPCS, PCL5c, PCL6